

MP330

OP Operate Panel



3.7-inch, homochromy

26 function keys, support area

Suitable for various PLC

Password protection and internal clock(Optional)

Key-press can be defined as function keys, partly replace the mechanical keys in control cabinet.

With backlight STN LCD

General Specifications

Display	Model	CCFL homochromy
	Using life	Up to 20000, Ambient temperature 25, 24 hours operation
	Display area	320*240
	Brightness	Can not be adjusted
	Language	Simplified Chinese/ Traditional Chinese, English, Japanese,
	Character	Chinese: 16*16 32*3 English : 8*16 16*32
	Key-press	42
Memory	Screen	4MB FlashROM
	Data	2KBSRAM
Interface	Download Port	RS232
	COM Port	RS232 /RS422

Function Specifications

Electrical Features	Input Voltage	DC24V
	Voltage Range	DC22V~DC26V
	Current Consumption	<260mA
	Allowable Momentary power-cut	Less than 10mS (Actual power-cut less than 1 second)
	Voltage Endurance	AC1000V, less than 20mA for 1 minute
	Insulated Resistance	Above 10M, DC500V
Environment	Operation Temperature	0 to 50
	Storage Temperature	-20 to 60
	Operation Humidity	10%RH to 90%RH (No condensing, dry bulb)
	Interference Rejection	Noise voltage;1500Vp-p, Pulse cycle:1uS , Druation:1 minute
Structure	Atmosphere	Free of corrosive gas
	Cooling Method	Natural air cooling
	External Dimension	283.3*193.9*50.0
	Cutout Dimension	270.8*158

