

## OP560-T OP Operate Panel

5.7-inch, 256-color TFT  
320\*234, 42 function keys  
Suitable for various PLC

Password protection and internal clock(Optional)

Key-press can be defined as function keys, partly replace the mechanical keys in control cabinet.



### General Specifications

Display	Model	256-color TFT
	Using life	Up to 20000, Ambient temperature 25, 24 hours operation
	Display area	320*234
	Brightness	Can not be adjusted
	Language	Simplified Chinese/ Traditional Chinese, English, Japanese,
	Character	Chinese: 16*16 32*3 English : 8*16 16*32
	Key-press	42
Memory	Screen	4MB FlashROM
	Data	2KBSRAM
Interface	Download Port	RS232
	COM Port	RS232 /RS422

### Function Specifications

Electrical Features	Input Voltage	DC24V
	Voltage Range	DC22V~DC26V
	Current Consumption	<260mA
	Allowable Momentary power-cut	Less than 10mS (Actual power-cut less than 1 second)
	Voltage Endurance	AC1000V, less than 20mA for 1 minute
Environment	Insulated Resistance	Above 10M, DC500V
	Operation Temperature	0 to 50
	Storage Temperature	-20 to 60
	Operation Humidity	10%RH to 90%RH (No condensing, dry bulb)
	Interference Rejection	Noise voltage;1500Vp-p, Pulse cycle:1uS , Druation:1 minute
Structure	Atmosphere	Free of corrosive gas
	Cooling Method	Natural air cooling
	External Dimension	283.3*193.9*50.0
	Cutout Dimension	270.8*158

