

## XMP3-18T

XMP series



Integrated PLC & HMI, owns the same functions as XC3 series, display area can be touched

Digital input: 10 points/optical couple isolated

Digital output: 8 points/relay

Easy edit, abundant functions LCD display: 192×64 pixel (3.7inh) ; use life up to 500,000 hours

Functional keys up to 26

Delicacy and precise keys

Use the same cable to Compile for HMI and PLC

IP65

Compact configure, save more space

### General specifications

|                               |   |
|-------------------------------|---|
| Input voltage                 | DC12V-DC24V                                     |
| Current Consumption           | Less than 10W (TYP2.0W)                         |
| Allowable Momentary Power-cut | Less than 20ms                                  |
| Voltage Endurance             | AC1000V-10mA 1 minute (signal and ground)       |
| Insulated Resistance          | DC500V- $\geq$ 10M $\Omega$ (signal and ground) |
| Operation Temperature         | 0~50°C  |
| Storage Temperature           | -10~60°C  |
| Ambient Humidity              | 20~85% (Non-condensing, dry bulb)               |
| Vibration Resistance          | 10~25Hz(X,Y,Z directions for 30 minutes 2G)     |
| Interference Rejection        | Noise voltage : 1000Vp-p                        |
| Atmosphere                    | Free of corrosive gas                           |
| Protect Configuration         | IP65F   |

Note : "-S" stands for internal timer and RS-485